

2 MP EXIR VF Bullet Camera**Key Features**

- 2 MP high-performance CMOS
- 1920 × 1080 resolution
- 2.7mm - 13.5mm vari-focal lens
- Ultra low light 0.005
- Day/Night switch, 120 dB true WDR
- EXIR 2.0, smart IR, up to 70 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP66

**Technical Specifications**

Camera	
Image Sensor	2 MP CMOS image sensor
Signal System	PAL/NTSC
Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.005 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25 (1/30) s to 1/50,000 s
Lens	2.7 mm to 13.5 mm Motorized Lens
Horizontal Field of View	102.4° to 31° Lens Mount Ø14
Day & Night	IR cut filter
Synchronization	Internal synchronization
Video Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Menu	
AGC	High/Medium/Low/Off
D/N Mode	Auto/Color/BW (Black and White)
BLC	Support
WDR	120 dB true WDR
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±25% Power Consumption Max. 7.7 W
Protection Level	IP66 Material Front Cover Metal, Main Body Metal, Bracket Metal
IR Range	Up to 70 m
Dimensions	256.4 mm × 83.3 mm × 78.2 mm
Weight	720 g (1.33 lb.)