

**5 MP Color24h Dome Camera****Key Features**

- 5 MP high-performance CMOS
- 2592\*1944 resolution
- 2.8 mm fixed focal lens
- Ultra low light
- Color24h, up to 25m Led distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP 67
- Built-in mic with high quality audio over coaxial cable (only TVI 4MP)

**Technical Specifications**

<b>Camera</b>	
Image Sensor	5 MP CMOS image sensor
Signal System	PAL/NTSC
Resolution	2592 (H) × 194 (V)
Min. Illumination	Ultra low light
Lens	2.8 mm or 3.6mm
Horizontal Field of View	93° (2.8mm) / 81° (3.6mm)
Day & Night	Color24h
Video Frame Rate	PAL: 5MP@25fps NTSC: 5MP@30fps
<b>Menu</b>	
AGC	High/Medium/Low/Off
D/N Mode	Auto/Color/BW (Black and White)
BLC	Support
WDR	OSD menu, 3D DNR, 120 dB true WDR
Functions	Brightness, Sharpness, DNR, Smart IR
<b>General</b>	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less
Power Supply	12 VDC ±15% Max. 5.5 W
Protection Level	IP67 Material Plastic
Led Range	Up to 25m
Dimensions	∅ 108 x 85(H) mm
Weight	400g