

2 MP EXIR Turret Camera



Key Features

- 2 MP high-performance CMOS
- 1920 × 1080 resolution
- 2.8 mm fixed focal lens
- Day/Night switch
- EXIR 2.0, smart IR, up to 20 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP66

Technical Specifications

| Camera | |
|--------------------------|--|
| Image Sensor | 2 MP CMOS image sensor |
| Signal System | PAL/NTSC |
| Resolution | 1920 (H) × 1080 (V) |
| Min. Illumination | 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | 1/25 (1/30) s to 1/50,000 s |
| Lens | 2.8 mm, 3.6 mm, 6 mm |
| Horizontal Field of View | 103° (2.8 mm), 80.7° (3.6 mm), 50.1° (6 mm) |
| Day & Night | IR cut filter |
| Synchronization | Internal synchronization |
| Video Frame Rate | PAL: 1080p@25fps NTSC: 1080p@30fps |
| Menu | |
| AGC | High/Medium/Low/Off |
| D/N Mode | Auto/Color/BW (Black and White) |
| BLC | Support |
| DWDR | Support |
| Functions | Brightness, Sharpness, DNR, Mirror, Smart IR |
| General | |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less (non-condensation) |
| Power Supply | 12 VDC ±15% Power Consumption Max. 4 W |
| Protection Level | IP66 Material Metal Case |
| IR Range | Up to 20 m |
| Dimensions | ∅ 82.6 mm × 69.66 mm (∅ 3.38" × 2.74") |
| Weight | 230 g (0.51 lb.) |