

5 MP EXIR Dome Camera



Key Features

- 5 MP high-performance CMOS
- 2592*1944 resolution
- 2.8 mm fixed focal lens
- Ultra low light
- EXIR 2.0, smart IR, up to 25m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP 67
- Built-in mic with high quality audio over coaxial cable (only TVI 4MP)

Technical Specifications

Camera	
Image Sensor	5 MP CMOS image sensor
Signal System	PAL/NTSC
Resolution	2592 (H) × 194 (V)
Min. Illumination	Ultra low light
Lens	2.8 mm
Horizontal Field of View	93° (2.8mm) / 81° (3.6mm)
Day & Night	IR cut filter
Video Frame Rate	PAL: 5MP@25fps NTSC: 5MP@30fps
Menu	
AGC	High/Medium/Low/Off
D/N Mode	Auto/Color/BW (Black and White)
BLC	Support
WDR	OSD menu, 3D DNR, 120 dB true WDR
Functions	Brightness, Sharpness, DNR, Mirror, Smart IR
General	
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), Humidity: 90% or less
Power Supply	12 VDC ±15% Max. 5.5 W
Protection Level	IP67 Material Metal
IR Range	Up to 25 m
Dimensions	Dimension Ø 109 x 93(H) mm
Weight	600g